

PLUSVAC 20

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Vacuum-moulded chambers, hygienic cleaning
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Anti-slip mat
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Additional sealing bar
- Voltage variants
- Carts
- ESD-Version
- Stronger sealing transformer
- Plug with phase inverter

Technical data

Chamber size (w x l x h /mm)	430 x 505 x 175
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	1 x 405 (2 x 405)
Sealing seam	double
Distance x (mm)	455 (400)
Position of sealing bar	
• Standard	front
• Option	back
Pump (cbm/h)	21
Power connection	400V / 3Ph+N+PE/50Hz
Power from (kW)	1,1
Max. bag (mm)	400 x 500
Insert plates	2
Outer dimensions (lid closed / w x d x h/mm)	480 x 655 x 385
Outer dimensions (lid open / w x d x h/mm)	480 x 655 x 920
Weight (kg)	62

The data in brackets are options.



Picture can show options.

fmk-web.de



PLUSVAC 21

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Vacuum-moulded chambers, hygienic cleaning
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Additional sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Stronger sealing transformer
- Plug with phase inverter

Technical data

Chamber size (w x l x h / mm)	430 x 505 x 175
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	1 x 405 (2 x 405)
Sealing seam	double
Distance x (mm)	455 (400)
Position of sealing bar	
• Standard	front
• Option	back
Pump (cbm/h)	21 (40 / 60)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	1,1 (1,5/1,9)
Max. bag (mm)	400 x 500
Insert plates	2
Outer dimensions (lid closed / w x d x h/mm)	480 x 655 x 975
Outer dimensions (lid open / w x d x h/mm)	480 x 655 x 1,550
Weight (kg)	65 (95 / 97)

The data in brackets are options.



PLUSVAC 23

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Additional sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Stronger sealing transformer
- Plug with phase inverter

Technical data

Chamber size (w x l x h /mm)	445 x 585 x 190
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	1 x 420 (2 x 420)
Sealing seam	double
Distance x (mm)	530 (485)
Position of sealing bar	
• Standard	front
• Option	back
Pump (cbm/h)	40 (60)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	1,5 (1,9)
Max. bag (mm)	420 x 600
Insert plates	2
Outer dimensions (lid closed / w x d x h/mm)	500 x 770 x 1,000
Outer dimensions (lid open / w x d x h/mm)	500 x 770 x 1,600
Weight (kg)	110 (112)

The data in brackets are options.



PLUSVAC 24

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bars
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter
- Higher lid

Technical data

Chamber size (w x l x h / mm)	640 x 480 x 200 (250)
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	2 x 455
Sealing seam	double
Distance x (mm)	(540)
Position of sealing bar	
• Standard	right, left
• Option	right or left
Pump (cbm/h)	40 (60)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	1,5 (1,9)
Max. bag (mm)	450 x 600
Insert plates	3
Outer dimensions (lid closed / w x d x h/mm)	710 x 665 x 1,010
Outer dimensions (lid open / w x d x h/mm)	710 x 665 x 1,500
Weight (kg)	115 (117)

The data in brackets are options.



PLUSVAC 25

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter
- Higher lid

Technical data

Chamber size (w x l x h / mm)	640 x 480 x 200 (250)
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	4 x 455
Sealing seam	double
Distance x (mm)	(540)
Position of sealing bar	
• Standard	right, left
• Option	right or left
Pump (cbm/h)	40 (60/106/151)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	2,1 (2,5/3,3/4,5)
Max. bag (mm)	450 x 600
Insert plates	3/chamber
Outer dimensions (lid closed / w x d x h/mm)	1,400 x 665 x 1,010
Outer dimensions (lid open / w x d x h/mm)	1,400 x 665 x 1,500
Weight (kg)	249 (251/278/287)

The data in brackets are options.



PLUSVAC 26

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Vacuum-moulded chambers, hygienic cleaning
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Additional sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter

Technical data

Chamber size (w x l x h /mm)	430x505x175
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	2 x 405 (4 x 405)
Sealing seam	double
Distance x (mm)	455 (400)
Position of sealing bar	
• Standard	front
• Option	back
Pump (cbm/h)	40 (60)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	1,5 (1,9)
Max. bag (mm)	400x500
Insert plates	2/chamber
Outer dimensions (lid closed / w x d x h/mm)	955x655x985
Outer dimensions (lid open / w x d x h/mm)	955x655x1,550
Weight (kg)	150 (152)

The data in brackets are options.



Picture can show options.

fmk-web.de



PLUSVAC 27

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter

Technical data

Chamber size (w x l x h / mm)	640 x 480 x 167
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	2 x 620
Sealing seam	double
Distance x (mm)	(380)
Position of sealing bar	
• Standard	front, back
• Option	front or back
Pump (cbm/h)	40 (60)
Power connection	400V/3PH+N+PE/50HZ
Power from (kW)	1,9 (2,3)
Max. bag (mm)	600 x 400
Insert plates	3
Outer dimensions (lid closed / w x d x h/mm)	710 x 665 x 1,010
Outer dimensions (lid open / w x d x h/mm)	710 x 665 x 1,500
Weight (kg)	145 (147)

The data in brackets are options.

